

Decal Removal & Install Instructions

REMOVAL

The following step-by-step instructions provide a good basic plan for removing old vinyl decals,

1. Peel decal off freezer. If decal is stuck or hard to remove use a heat gun on low and apply a small amount of heat.
2. Once you have peeled all of the decal off, you will have to clean the adhesive off the surface with a non-abrasive cleaner to remove any glue or debris.
3. Clean the surface with soap and water.
4. At this point, you are done.

SURFACE PREPARATION

All surfaces should be considered dirty and should be cleaned prior to application of vinyl lettering or graphics. Clean the area with soap and water, where the vinyl will be applied. Then, rinse area thoroughly and dry.

TEMPERATURE REQUIREMENTS

Air and application surface should be above 70 degrees F. Best conditions are between 70 - 80 degrees F.

APPLICATION



Step 1
Peel and fold backing paper from decal about 2" down from top.



Step 2
Line decal up perfectly to the top of freezer. Use freezer sides to make sure graphic will not run off.



Step 3
From right to left begin squeegeeing decal to freezer. Press firm to apply properly.



Step 4
Lift up decal and peel about 6 inches of backing paper from decal.



Step 5
Begin squeegeeing. Remove the backing paper at the same rate as squeegeeing, so only 6 inches of decal is exposed at one time.



Step 6
Continue squeegeeing while removing backing paper slowly working down freezer side until done.

